



**MICRO POWER**  
**CENTRAL SUPPLY EMERGENCY LIGHT**  
 SERIES : CTX12-100



**BATTERY**  
**ISO 9002**



## SPECIFICATIONS

INPUT VOLTAGE	:	220 V AC/50Hz +/-10%
TYPE OF BATTERY	:	SEALED LEAD ACID
MODE OF OPERATION	:	NON-MAINTAINED
OPERATING TEMPERATURE	:	Ta 40 C
CHARGER	:	TWO STEP CONSTANT VOLTAGE & CURRENT LIMIT 1 st STEP.....14.20V - 14-50V 2 nd STEP.....13.40V - 13-60V
CHARGER CURRENT	:	LIMITS CURRENT TO 100% OF FULL LOAD : CURRENT DOWN TO SHORT CIRCUIT CONDITION
PROTECTION	:	AC.FUSE / DC.FUSE / LOW VOLTAGE CUT OFF TO PREVENT BATTERY OVER DISCHARGE
PANEL METERS	:	DC.BATTERY VOLTAGE/DC.CHARGE CURRENT
CONSTRUCTION	:	ELECTRO GALVANISED STEEL CASE EPOXY POWER COATED
COMPLIANCE	:	IEC. 592-2-22
WEIGHT	:	70 KG
OPTION	:	AUTOMATIC TEST MOUNTHLY EXERCISE : REMOTE TEST WIRELESS : TIME DELAY 1 UP TO 10 MINUTES : EXHAUST-FAN

MODEL	BATTERY SEALED LEAD ACID	LAMP HEAD	LAMP WATT	DURATION	WEIGHT
CTX12-100C	12V - 100Ah	SQUARE	400	2 HR.	70 KG.