




**MICRO POWER**  
**SELF-CONTAINED EMERGENCY EXIT SIGN**  
 SERIES : ELD



**BATTERY**  
**ISO 9002**



Double-Sided Box Exit Sign  
**IP30 Class 1**

This Double-Sided Exit Sign is specially designed with a gear tray which is removable and is independent of the housing to facilitate ease of installation, maintenance and replacement of lamps. It also enhances the Slim Construction of the Box and at the same time provides even and Homogenous Light Distribution.

## SPECIFICATIONS

MODE OF OPERATION	:	<input type="checkbox"/> MAINTAINED	<input type="checkbox"/> SUSTAINED
LAMP	:	<input type="checkbox"/> 1 X 10W.	<input type="checkbox"/> 2X10W. FLUORESCENT LAMP
RATE DURATION	:	2 HRS & OTHERS	
MAIN SUPPLY	:	220 VOLT, 50Hz & OTHERS	
POWER CONSUMPTION	:	4VA / 13VA	
BATTERY	:	HIGH TEMP NICKLE CADMIUM	
CHARGER	:	AUTOMATIC CONSTANT CURRENT	
CHARGER MONITOR	:	RED L.E.D. Ø 5mm.	
TEST FACILITY	:	MICRO SWITCH	
SAFETY FEATURE	:	LOW VOLT CUT-OFF PREVENTING BATTERY OVER DISCHARGE	
FITTING CONSTRUCTION	:	ELECTRO GALVANISED STEEL WITH EPOXY POWDER COATING	
DIFFUSER	:	FIRE RETARDANT MOULDED ACRYLIC	
LEGEND	:	ISO GREEN, OTHER LEGEND OPTIONAL	
MOUNTING	:	WALL OR CEILING	
CABLE ENTRY	:	Ø 20mm. K/O HOLE	
COMPLIANCE	:	CP19, SS263 : PART 2, ICE 598-2-22	

MODEL	BATTERY	LAMP (WATT)	SIDE	DURATION	WEIGHT (GROSS)
ELD 1FL10N	NI-CD HI-TEMP 2.4V4.0Ah	FLUORESCENT 1 X 10W.	DOUBLE	2 HOURS	3.0 KG.